



产品规格书

PRODUCT SPECIFICATION

| | |
|--|--|
| 客户名称Buyer Name | |
| 客户料号Buyer Part No. | |
| 客户承认签章 Buyers Approval & Signatures | |

| | | | |
|-----------------------------|--------------------------------|---------------|-----|
| 文件编号Spec No. | | 版本 | A/1 |
| 品名描述 Product Description | 圆柱直流马达 Cylindrical DC motor | | |
| 型号Part No. | VZ7AL2H1690002 | | |
| 送样日期Date | | | |
| 设计Designed by | 审核Checked by | 批准Approved by | |
| | | | |
| 2020.07.01 | 2020.07.01 | 2020.07.01 | |

www.vybronic.com
sales@vybronic.com

规格书内容/Contents

| | |
|---|-----|
| 1、适用范围/ General Scope | 3/9 |
| 2、使用条件/ Operating Conditions | 3/9 |
| 3、测定条件/ Measuring Conditions | 3/9 |
| 4、机械要求/ Mechanical Specifications | 3/9 |
| 5、性能特征/ Performance and characteristics | 4/9 |
| 6、可靠性/ Reliability | 5/9 |
| 7、要求/ Requirements | 6/9 |
| 8、使用时注意事项/ Attentions | 6/9 |
| 9、包装/ Packaging | 7/9 |
| 10、外形图/ Outline Drawing | 8/9 |
| 11、修改记录/ Revision History | 9/9 |

1. 适用范围/ General Scope

本说明书适用于圆筒式永磁直流电机 VZ7AL2H1690002 型

This specification applies to cylindrical permanent-magnetic motors DC model VZ7AL2H1690002

2. 使用条件/ Operating Conditions

| 项目/Item | 规格/Specifications | 条件·备注/Conditions & Remarks |
|--------------------------------------|---|--|
| 2-1 额定电压 Rated voltage | 1.5V DC | |
| 2-2 额定负荷 Rated load | 振子 Counterweight | 见 10. 外形图 As specified in 10. Outline Drawing |
| 2-3 旋转方向 Rotation | C.W/C.C.W (clockwise or counter clockwise) | |
| 2-4 马达位置 Motor position | 全方位 All position | |
| 2-5 使用电压范围 Operating voltage | 1.0~1.8V DC | |
| 2-6 使用环境 Operating environment | -30 ~ 70℃, 常湿 /Ordinary Humidity:65±20%RH | 无水气凝结 No condensation of moisture |
| 2-7 保存环境 Storage environment | -40 ~ 80℃, 常湿 /Ordinary Humidity:65±20%RH | 无水气凝结 No condensation of moisture |

3. 测定条件/ Measuring Conditions


| 项目/Item | 规格/Specifications | 条件·备注/Conditions & Remarks |
|-----------------------------|--------------------------------|--|
| 3-1 温度 Temperature | 20±2℃ | |
| 3-2 湿度 Humidity | (63%~67%) RH | |
| 3-3 位置 Motor position | 轴向水平 Motor shaft horizontal | 将马达固定在试验台上 Lock the motor in a test fixture |

标准测试条件为温度 20℃，湿度 65%。如无疑异，也可在温度 5~35℃、湿度 45~85%的条件下测试。马达测试时，放置方向为轴向水平。/The measurement at 20℃ & 65%RH is standard. If the judgment is not questionable, recognize measurement at 5℃ to 35℃ & relative humidity 45% to 85%. Direction of motor is shaft horizontal.



4. 机械要求/ Mechanical Specifications

| 项目/Item | 规格/Specifications | 条件·备注/Conditions & Remarks |
|---|--|---|
| 4-1 结构 Configuration | 见 10. 外形图 As specified in 10. Outline Drawing | Outline drawing No: VZ7AL2H1690002 |
| 4-2 外观 Appearance | 不含有机机械损坏及不充分的浸蚀等。 There shall be no evidence of mechanical damage and shall not have inadequate corrosion and so on | 目测（容许范围根据样品外形） Visual examination(allowable extent is based on boundary sample) |
| 4-3 轴向间隙 Shaft end play | 0.1mm~0.3mm | |
| 4-4 振子固定力 Holding strength of vibration weight | 49N (5kgf) Min | |

5.性能特征/Performance and characteristics

| 项目/Item | | 规格/Specifications | 条件·备注/Conditions & Remarks |
|---------|-------------------------------|-------------------|---|
| 5-1 | 额定转速 Rated speed | 11,500±2,500 rpm | 在额定电压和额定负载(振子)下。 At rated voltage and rated load (Counterweight). |
| 5-2 | 额定电流 Rated current | 370 mA Max | |
| 5-3 | 堵转电流 Stall current | 1,000 mA Max | 在额定电压下。 At rated voltage |
| 5-4 | 起动电压 Starting voltage | 1.0V DC Max | 在额定负载(振子)下电枢的任意位置。 At rated load (Counterweight) any position of rotor. |
| 5-5 | 绝缘电阻 Insulation resistance | 1MΩ Min | 在 100V 直流下, 端子和机壳间 At DC 100V between Terminal and case. |
| 5-6 | 端子阻抗 Terminal resistance | 1.6 Ω (±20%) | 在 20℃ 下 At 20℃ |
| 5-7 | 机械噪音 Mechanical noise | 50dB(A)Max | <p>在额定电压、额定负载(振子)下 背景噪音: 不大于 28dB.A 计权 测试仪器: B&k 夹具重量: 700g At rated voltage and rated load (Counterweight). Back ground noise 28dB(A) Max Measuring instruments: B&k Weight of jig:700g</p>  <p>Fig. A Fig. B Fig. C</p> |

6. 可靠性/Reliability

| 项目/Item | 规格/Specification | 判定标准/Judgment | | | | | | | | | | | | |
|------------------------------------|--|--|------------|------------|------------------|------------|------------|----------------|----|--------------|-----|-----|------------------|--|
| 6-1 寿命 Life time |  <table border="1" data-bbox="359 533 997 728"> <tr> <td>位置 Position</td> <td>电压 Volt</td> <td>负荷 Load</td> <td>温度 Temp</td> <td>湿度 Humi</td> <td>寿命 Life</td> </tr> <tr> <td>轴水平 Horizon</td> <td>额定</td> <td>Weight 振子</td> <td>20℃</td> <td>65%</td> <td>20,000 Cycles</td> </tr> </table> | 位置 Position | 电压 Volt | 负荷 Load | 温度 Temp | 湿度 Humi | 寿命 Life | 轴水平 Horizon | 额定 | Weight 振子 | 20℃ | 65% | 20,000 Cycles | <p>在常温常湿下放置 2h 后, 马达应符合项 7-1 的要求。</p> <p>After 2 hours exposure in ordinary temperature and humidity, Motors shall be approved as specified in item 7-1.</p> |
| 位置 Position | 电压 Volt | 负荷 Load | 温度 Temp | 湿度 Humi | 寿命 Life | | | | | | | | | |
| 轴水平 Horizon | 额定 | Weight 振子 | 20℃ | 65% | 20,000 Cycles | | | | | | | | | |
| 6-2 低温放置 Low temp exposure | 温度 /Temperature: $-40\pm 2^{\circ}\text{C}$ 时间 /Time: 96h | <p>在常温常湿下放置 2h 后, 马达应符合项 7-2 的要求。</p> <p>After 2 hours exposure in ordinary temperature and humidity, Motors shall be approved as specified in item 7-2.</p> | | | | | | | | | | | | |
| 6-3 高温放置 High temp. Exposure | 温度 /Temperature: $60\pm 2^{\circ}\text{C}$ 时间 /Time: 96h | | | | | | | | | | | | | |
| 6-4 湿度放置 Humidity exposure | 温度 /Temperature: $40\pm 2^{\circ}\text{C}$ 湿度 /Humidity: 90~95%RH 放置时间 /Exposure time: 96h 无水气凝结/No condensation of moisture | | | | | | | | | | | | | |
| 6-5 振动 Vibration | 全振幅 /Displacement: 1.5mm (p-p) 频率 /Frequency: 10 ~ 55Hz 加速度 /Acceleration: 22m/s^2 周期 /Period: 20min 完成 10~55~10Hz /20 Minutes log sweep 10~55~10Hz 方向 /Direction: x, y, z 时间 /Time: 每个方向 2h /Each 2 hours | | | | | | | | | | | | | |
| 6-6 自然跌落 Free fall | 试验状态/Test state: 将马达固定在约 75 克 (包括马达本身) 的物体上, 落向水泥地面。 Set the motor to the approximately 75g (include the motor) weight of block drop the motor on the concrete floor. 高度 /Height: 1.5m 方向 /Direction: 6 个面 / 6 faces 次数 /Number of times: 每个面 2 次 / Twice 2 each | <p>测试结果应符合项 7-2 的要求。</p> <p>After the test motors shall be approved as specified in item 7-2.</p> | | | | | | | | | | | | |
| 6-7 热冲击 Heat shock test | 试验循环 /Test cycle :20 cycles  | <p>在常温常湿下放置 2h 后, 马达应符合项 7-2 的要求。</p> <p>After 2 hours exposure in ordinary temperature and humidity, Motors shall be approved as specified in item 7-2.</p> | | | | | | | | | | | | |

7. 要求/Requirements

| 项目/Item | | 判定基准 / Requirements |
|---------|----------------|---|
| 7-1 | 表 A Table A | 1) 额定转速/Rated speed: 不大于初始值±50%/Initial data±30% max 2) 额定电流/Rated current: 不大于初始值±50%/Initial data±30% max 3) 起动电压/Starting voltage: 1.3V DC Max |
| 7-2 | 表 B Table B | 1) 额定转速/Rated speed: 不大于初始值±30%/Initial data±30% max 2) 额定电流/Rated current: 不大于初始值±30%/Initial data±30% max 3) 起动电压/Starting voltage: 1.3V DC Max |

8. 使用时注意事项/Matters to be paid attention to when using motor

8-1 电机在运输过程中应小心轻放，避免严重碰撞敲击引起的电机机身和性能受损。(Please lay the motors carefully in transportation to avoid any serious damage to the motor body or its electric function because of collision.)

8-2 请按照规格书中规定的第 2 条(使用条件)来使用和存储电机，否则会影响电机性能。(Please use and storage motors according to N0.2 item (Operating Conditions) in specification, or else motor characteristics would be affected.)

8-3 请在 6 个月内使用。在使用和打开马达外包装时请避免水气凝结。(Make arrangement to limit the storage period to 6 months or less. Condensation of atmosphere must be avoided in motor usage or opening the packaging of the motor.)


8-4 马达应适当的操作、储存和运转环境中均不可存在腐蚀性气体。例如：H₂S、SO₂、NO₂、CL₂ 等。另外存储环境中不可有诸如硅、氰、甲醛水和苯酚等能放射出腐蚀性气体的物质，在电机的机械构造或装置中，如果存在腐蚀性气体，那么这会引起马达不运转。(For proper operation. storage and operating environment must not contain corrosive gases. For example H₂S. SO₂. NO₂. CL₂. etc. In addition storage environment must not have materials that emit corrosive gases especially from silicon. cyanic. formalin and phenol group. In the mechanism or the set. existence of corrosive gases may cause no rotation in motor.)

8-5 请通电后不要长时间堵住机轴，并且马达转动时不要触碰振子。(Please don't stall the shaft for a long time after powering, and not to touch the weight when motor is rotating.)


8-6 马达轴向间隙处不应有杂物（如颗粒、纤维物、头发、胶带、胶水等）(There should be no sundries (such as grain, fibre, hair, small tape, glue etc.) in the shaft end play.)

9. 包装/Packaging


圆柱马达包装 Packaging drawing of cylindrical motor



50PCS (1 tray) × 10



500PCS (1 bundle) × 6


包装试验要求
1. 标准

- (1) 整箱重量小于等于9kg的, 跌落高度设定为75cm.
- (2) 整箱重量大于9kg但小于等于23kg的, 跌落高度设定为60cm.

2. 试验方法:

跌落要求为六面三棱一角.

- (1) 六面: 先从最大两面跌, 然后是中间大小的两面, 最后跌最小的两面, 一共六次.
- (2) 三棱: 指任选三条同一角的棱, 跌落秩序: 最长棱, 中间长度, 最短的, 一共三次.
- (3) 一角: 指上一步三条棱所组成的角, 跌落一次.

3. 判定基准

经过跌落试验后, 产品外观、性能无不良.

Package Test Requirement:
1. Criteria

- (1) The weight of the whole carton less than 9kg, the dropping height is 75cm.
- (2) The weight of the whole carton more than 9kg and less than 23kg, the dropping height is 60cm.

2. Test Methods:

Dropping requirement is 6 faces, 3 arris, 1 angle.

- (1) 6 faces: First dropping with two biggest faces, then dropping with another two middle faces, at last dropping with two smallest faces, once per face, total 6 faces.
- (2) 3 arris: Choose any 3 arris which make up of the same the angle, the dropping sequence is the longest arris, middle arris, shortest arris. Total 3 times.
- (3) 1 angle: Point to the angle which is made up with the 3 arris in the above step. Dropping for 1 time.


3. Judgement Criterion

After drop test, no evidence of damage on the appearance and performance.

Remarks:


- 500PCS/CTN: 24cm × 17.5cm × 27.5cm
 1000PCS/CTN: 34cm × 24cm × 27.5cm
 2000PCS/CTN: 47cm × 34cm × 27.5cm
 3000PCS/CTN: 51cm × 47cm × 27.5cm

OPP TAPE



10. 外形图/Outline Drawing

- 技术要求/Technical requirement**
1. 额定电压/Rated voltage: 1.5V
 2. 额定电流/Rated current: 370mA Max
 3. 额定转速/Rated speed: 11,500 ± 2,500rpm
 4. 堵转电流/Stall current: 1,000mA Max
 5. 端子阻抗/Terminal resistance: 1.6Ω(±20%)
 6. 启动电压/Starting voltage: 1.0V Max
 7. 轴向间隙/Shaft end play: 0.1~0.3mm
 8. 导线规格/Lead wire spec: AWG30 UL1571
 9. 所有尺寸为A向压紧后的尺寸(不包括轴向间隙)
/Overall length is measured after counterweight being pressed against body in direction A. (Shaft end play is not included.)
 10. 未注线性公差为/Unmarked tolerance: ±0.1mm



| | | | |
|----------|-----|----------------|------------|
| 借(通)用件登记 | | Vybronic | |
| 底图总号 | | 外形图 | |
| 签字 | | VZ7AL2H1690002 | |
| 日期 | | 阶段标记 | 重量 比例 |
| | | 共 页 | 5:1 |
| | | 第 页 | |
| 设计 | 郭梦秋 | 更改文件号 | 项瑞莹 |
| 校对 | 汪丰华 | 2009.09.16 标准化 | 2009.09.16 |
| 审核 | 郑景海 | 2009.09.16 | 2009.09.16 |
| 工艺 | 刘林兵 | 2009.09.16 批准 | 2009.09.16 |

11. 修改记录/Revision History

| 修改号 Rev. No. | 日期 Rev. Date | 页码 Page No. | 修改项目 Revised Item | 更改原因 Reason |
|-----------------|-----------------|----------------|---|----------------|
| A/0 | 2009.09.16 | / | 产品颁布/ Release for Production | |
| A/1 | 2020.07.01 | / | changed company name from JINLONG MACHINERY to VYBRONICS, changed part # from Z7AL2H1690002 to VZ7AL2H1690002 | Rebranding |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |